



Nylon rivet SR

Nylon rivet SR

Material: Nylon rivets, qualified NYLON66 (black or white), fire rating 94V-2, not easy to aging, high insulation.

Usage: The first board and was fixed plate drilling, and then squeezed into the product, you can make the two plates together.

Uses: PC board and the board fixed, replace the screws, without tools to complete the assembly.

Special offer a limited number of while stocks last, the large price is better

Nylon rivets nylon rivets SR

Specification

Item no	PCS	price
SR-0612KB	2000	0.54
SR-0612KW	13758	0.35
SR5-429	5000	0.42
SR6-535	990	0.477
SR8-102	800	0.62
SR9-611	990	0.81
SR9-942	1393	0.618
SG2L-SPL2LW(male)	541	0.165
SG2L-SPL2LW(female)	659	0.165
SG3M-SPB3MB(male)	4000	1.004
SG4L-SPL4LB(male)	1450	1.004
SG4L-SPL4LB(female)	1000	1.004
SR7-101	880	0.41
SR5-187	1760	0.421
SG1L-SPL1LB(female)	3570	1.004
SR5-003	1886	0.062
SR6-202	2450	0.590
SR6-580	6305	0.365
SR5-506	1600	0.32
SRHR4100	3330	0.548
SRHR3035	2000	0.456
NCR32-1	375	0.395
NCR48-2	2480	0.456
SR5-8.5B	19000	0.335
SR5-9.5W	18640	0.335
SR3-6.5W	20000	0.213
SRS-3045	19000	0.42
SR6-8W	977	0.487
SR6-6W	985	0.487
SR6-6B	712	0.487
SR3-7.5B	1000	0.213

SR2-6.4W	1000	0.335
DF5-491	900	0.28
SR5-4.5W	1900	0.335
SG3M-SPB3MB(female)	4960	1.004
SG1L-SPL1LB(male)	3650	1.004